



► UPS-DUO STANDARD VOLUME

Precise, proven metering technology. Accurate 1:1 delivery of Urethane, Epoxy, Silicone or Polyester materials, it is ideal for materials used in coating, adhesives, casting, and laminating resins.

DESCRIPTION:

► SYSTEM FEATURES

The Standard Volume Duo Unit features:

- Precise, proven metering technology
- 1:1 delivery of urethane, epoxy, silicone or polyester materials
- Ideal for materials used in coatings, adhesives, casting and laminating resins
- 1:1 Pro Gun

► SPECIFICATIONS

STANDARD VOLUME - DUO-54646

Output Cap: Depending on materials: 10 lbs-30 lbs per min.

Avg. Air Consumption: 10 to 15 CFM

Mix Ratio: 1:1

Pump Ratio: 8:1

LOW VOLUME - DUO-52424

Output Cap: 5 lbs-20 lbs

Avg. Air Consumption: 10 to 15 CFM

Mix Ratio: 1:1

Pump Ratio: 15:1

► OPTIONS

- Heaters
- Heated hose sets
- Stainless steel fluid sections
- Portable Carts
- Booms



Knoxville

Corporate Headquarters
2030 Falling Waters Rd., Suite 350
Knoxville, TN 37932
865-686-5670

Kent

Manufacturing Center
1862 Ives Ave.
Kent, WA 98032
253-854-2660

Knoxville

Service Center
642 Barbrow Lane
Knoxville, TN 37932
865-321-8809

Goshen

Service Center
320 North Main St.
Goshen, IN 46528
574-534-1434

Oldsmar

Service Center
146 Dunbar Avenue, Unit A
Oldsmar, FL 34677
727-573-2955

Canada

72 Beauvais
Delson, Qc J5B 1W8
888.538.4330

► For more information about adding the UPS-Duo Standard Volume to your operation, or any of your adhesive dispensing needs, visit Magnum Venus Products at www.mvpind.com.